

IND4



APPLICATION: IND-4

LEGACY MODEL: A2366

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32" ⁶⁵	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs. @ psi	WT. lbs.
813421-74	1400R24	**	193	A5	10.00/1.5	60	55.9	15.0	24.3	161	25,400@145	485
813891-74	1600R25	***	200	A5	11.25/2.0	68	61.1	16.9	27.4	182	30,900@145	794
813893-74	1800R25	***	207	A5	13.00/2.5	81	65.9	19.8	30.6	203	38,600@145	970
813070-74	1800R33	***	214	A5	13.00/2.5	91	74.4	19.8	33.3	222	46,700@145	1,202

RUBBER COMPOUND:

CUT RESISTANT	<input type="checkbox"/>
HEAT RESISTANT	<input type="checkbox"/>
STANDARD	<input checked="" type="checkbox"/>

The Aeolus AIN46 is purpose built for use in port applications. It is engineered with an enhanced casing to deliver excellent stability and superior load carrying capacity. The AIN46 delivers a comfortable ride resulting in reduced operator fatigue.

Features & Benefits:

- Superior durability and reduced cost per hour
- Exceptional stability
- High speed capacity
- Wear and cut resistant tread compound

Applications:

- Industrial forklifts



AEOLUS OTR TIRES

Caption:

Description:

Dimensions: 540 x 700

aperture: 0

credit:

camera:

caption:

created_timestamp: 0

copyright:

focal_length: 0

iso: 0

shutter_speed: 0

title:

orientation: 1