

6/10/2015

AR28 - Aeolus Tyres - Aeolus Tyres



AR28



AR28:

- Longer life (compared to A2225)
- Reduced rolling resistance (compared to A2235)
- Excellent resistance to damage
- Reducing vibrations
- Suitable for speeds up to 80km/h



From today the improved Aeolus AR28 tyre is available in Europe. This is the successor of the A2235 tyre for mobile cranes, also known as Aeolus' 'highway service' tyre. Both the 385/55R25 (170F) and the 445/55R25 (174F) are available directly from stock. Aeolus has the right tyre available for a wide range of jobs, including very specific and hard jobs.

The AR28 is designed for mobile cranes that are deployed both on- and off-road. The tyre has a tread compound which gives it a so called progressive self-cleaning capacity and therefore had excellent traction in tough demanding conditions.

Size	Star rating	RIM	New Tyre Dimension		Load(kg)		Pressure(kpa)		L/SS		TRA CODE	Tread depth(mm)	Valve
			Width(mm)	Dis(mm)	15 km/h	80 km/h	10 km/h	80 km/h	18 km/h	80 km/h			
385/55R25	3	10.00/1.5	389	1363	6000		900		170F		E-2	24	
445/55R25	3	11.25/2.0	444	1488	7300		900		174F		E-2	28	

<http://www.aeolus-tyres.eu/pl/otr/ar28>

1/1

Caption:

Description:

Dimensions: 494 x 700

aperture: 0

credit:

camera:

caption:

created_timestamp: 0

copyright:

focal_length: 0

iso: 0

shutter_speed: 0

title:

orientation: 1